











URBAN FIXED LIGHT WINDOW

The Urban Fixed Light Window has been designed to provide a clean and streamlined appearance to complement the range of Urban operable windows and doors. Fixed light windows can be coupled to all windows within the Urban range or used independently where openings are not required. Frame the perfect view, maximise natural light and enjoy the great outdoors with an Urban fixed light window to expand your view.

FEATURES AND BENEFITS

- Thermally efficient frame design
- Single and double glazing options
- Render frame options
- Range of couplers available for large fixed lights
- Bushfire and Acoustic ratings
- Compatible with other Urban products

MAXIMUM PERFORMANCE

Serviceability Pressure	4500Pa
Ultimate Pressure	8000Pa
Water Penetration	450Pa

FRAME DIMENSIONS

Standard	48.5mm
Wide Frame	95.0mm

MAXIMUM RECOMMENDED SIZE

Window	Height	Width
Single *	2700mm	2700mm
Combination **	2400mm	1500mm

GLAZING CAPACITY

Single Glazed	3mm-14mm
Double Glazed	16mm-25mm

^{*} Max Area = 4.0m²

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf			
CAP-152-01	6Clr/6/6Clr	3.6	0.64	0.7	0.01			
CAP-152-02	6ET/6Ar/6Clr	2.7	0.56	0.65	0.01			
CAP-152-03	4Clr/10/4Clr	3.3	0.68	0.72	0.01			
CAP-152-04	4Gy/10/4Clr	3.3	0.51	0.45	0.01			
CAP-152-05	4Clr/10Ar/4Clr	3.2	0.68	0.72	0.01			
CAP-152-06	4Gy/10Ar/4Clr	3.2	0.50	0.45	0.01			
CAP-152-19	AGG PLUS Clr 4/12/4	2.1	0.55	0.73	0.01			
CAP-152-20	AGG PLUS Clr 5/12/5	2.1	0.55	0.72	0.01			
CAP-152-21	AGG PLUS Clr 6/12/6	2.1	0.54	0.71	0.01			
CAP-152-22	AGG PLUS Gy 4/12/4	2.1	0.40	0.45	0.01			
CAP-152-23	AGG PLUS Gy 6/12/6	2.1	0.33	0.35	0.01			
CAP-152-28	AGG MAX Clr 6/12/6	2.1	0.26	0.58	0.01			

ALUMINIUM (258 646)

Capral.com.au Capral Limited ABN 78 004 213 692 October 2021

^{**} Max Area = 2.8m²