




urbanplus[™]
DESIGNER
DOUBLE HUNG WINDOW

CAPRAL
ALUMINIUM



URBAN PLUS DOUBLE HUNG WINDOW

The Urban Plus Double Hung Window features a substantial outer frame allowing for large configurations with a modern, architectural aesthetic.

Bold mitred sash profiles sit within a clean square cut frame demonstrating the simplicity and style which are hallmarks of the Urban Plus range. High quality operating hardware and a simple sash release system for easy cleaning from within the building make the Urban Plus Double Hung Window the ideal choice for elevated applications. This system incorporates integrated finger pulls and high quality latch hardware to further enhance the functionality of this modern take on a classic window style.

FEATURES AND BENEFITS

- Premium quality 76mm architectural framing system
- Large capacity single and double glazing options
- Height adjustable sash panels
- AGS 300/325 and 400/425 Narrowline compatible for seamless integration
- Compatible with the full range of Urban Plus window suites
- Integrated insect and security screening options
- Exclusively designed components to improve the system's performance and function
- Provision for High, Low and Side Lights

MAXIMUM PERFORMANCE

| | |
|-------------------------|--------|
| Serviceability Pressure | 2200Pa |
| Ultimate Pressure | 3800Pa |
| Water Penetration | 350Pa |

FRAME DIMENSIONS

| | |
|-------|------|
| Depth | 76mm |
|-------|------|

MAXIMUM RECOMMENDED SIZE

| | |
|-------------|--------|
| Sash Height | 1200mm |
| Sash Width | 1200mm |
| Sash Weight | 20.4kg |

GLAZING CAPACITY

| | |
|---------------|-------------|
| Single Glazed | 4mm - 10mm |
| Double Glazed | 16mm & 18mm |

WINDOW ENERGY RATINGS

| Window ID | Glazing | Uw | SHGC | T _w | Air Inf |
|------------|----------------|-----|------|----------------|---------|
| CAP-528-01 | 6.38CPGy | 4.9 | 0.37 | 0.27 | 0.21 |
| CAP-528-02 | 6.38CPNtl | 4.9 | 0.38 | 0.41 | 0.21 |
| CAP-528-03 | 6.38CPClr | 4.9 | 0.50 | 0.57 | 0.21 |
| CAP-528-04 | 6.38ClrLam | 6.3 | 0.57 | 0.61 | 0.21 |
| CAP-528-05 | 6ET | 4.9 | 0.50 | 0.57 | 0.21 |
| CAP-528-06 | 4Clr | 6.4 | 0.62 | 0.63 | 0.21 |
| CAP-529-01 | 4Clr/10/4Clr | 4.3 | 0.56 | 0.58 | 0.21 |
| CAP-529-02 | 4Clr/10Ar/4Clr | 4.2 | 0.56 | 0.58 | 0.21 |
| CAP-529-03 | 4Gy/10Ar/4Clr | 4.3 | 0.41 | 0.36 | 0.21 |
| CAP-529-04 | 4ET/10Ar/4Clr | 3.6 | 0.47 | 0.53 | 0.21 |
| CAP-529-05 | LB Gy 4/10/4 | 3.5 | 0.31 | 0.36 | 0.21 |
| CAP-529-06 | LB Clr 4/10/4 | 3.5 | 0.45 | 0.58 | 0.21 |



1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
July 2021

View full list of Residential WERs ratings at capral.com.au