





URBAN PLUS SLIDING DOOR DOOR

The Urban Plus sliding door has been designed to span wide openings and maximise views. Available in sliding and multi-stack configurations the Urban Plus Sliding Door can span openings up to 12m wide and 2.7m high.

A number of performance sill options to suit standard and exposed locations provide great flexibility in the application of the system. Clean bold lines are hallmarks of this design and can be complemented with the elegant aesthetics of Caprio or Caprice hardware to create a defining feature within the home.

With single and double glazing options the Urban Plus Sliding Door offers flexibility to achieve stringent energy provisions and meet building code requirements across Australia.

FEATURES AND BENEFITS

- Available as Standard or Multistack configurations with or without screen tracks.
- XO, OXO, XXO, OXXO, OXXXXO
- Low Profile (18.5mm), Standard (48.5mm) & HP (67mm) Sills available.
- Premium quality 125mm architectural framing systems
- Complementary hardware from the Caprio and Caprice ranges

- Single and Double glazing options.
- Ability to site or factory glaze.
- Unique sill tray design seamlessly connects main frame to screen tracks
- Linear Grate drain solution possible using aluminium or SS grates
- Integrated fixed light framing system
- Integrated screen tracks which easily accommodates Amplimesh security door or flyscreen door.

MAXIMUM PERFORMANCE

Serviceability Pressure	4000Pa
Ultimate Pressure	6200Pa
Water Penetration	450Pa

FRAME DIMENSIONS

Depth	125mm

MAXIMUM RECOMMENDED SIZE

Height	2700mm
Width	2200mm
Weight	200kg

GLAZING CAPACITY

Single Glazed	4-10mm
Double Glazed	18-24mm

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tvw	Air Inf
CAP-540-01	6.38ComPlsGy	4.5	0.40	0.31	0.03
CAP-540-02	6.38ComPlsNtl	4.5	0.41	0.46	0.03
CAP-540-03	6.38ClrLam	6.1	0.63	0.69	0.03
CAP-540-04	6.38ComPlsClr	4.5	0.55	0.64	0.03
CAP-540-05	6ETech	4.5	0.56	0.64	0.03
CAP-540-06	6Clr	6.2	0.66	0.69	0.03
CAP-541-01	LBClr6/12/6	2.9	0.47	0.64	0.03
CAP-541-02	LBGy6/12/6	2.9	0.28	0.30	0.03
CAP-541-03	6ETech/12Ar/6Clr	3.0	0.50	0.58	0.03
CAP-541-04	6Clr/12/6Clr	3.8	0.58	0.63	0.03
CAP-541-05	6Clr/12Ar/6Clr	3.7	0.58	0.63	0.03
CAP-541-06	6Gy/12/6Clr	3.8	0.38	0.30	0.03

View full list of Residential WERS ratings at capral.com.au



1800 ALUMINIUM (258 646) capral.com.au Capral Limited ABN 78 004 213 692 January 2022