





# **URBAN PLUS HINGED DOOR**

The Urban Plus Hinged Door system features smooth flat panel profiles with an integrated bead to achieve a modern yet classic appearance. Capable of accommodating large high-performance double glazing to easily achieve enhanced thermal comfort and performance.

Offering a multitude of options, including open-in, open-out, single and double doors, the Urban Plus Hinged Door also has the ability to be fully or partially glazed with glass or the aluminium panel system.

## FEATURES AND BENEFITS

- 36mm and 46mm panel thickness
- Door panel also compatible with commercial framing
- Premium quality 125mm architectural framing system
- Exclusively designed components to improve the system's performance and function
- Single and double glazing options
- Fully compatible with the Caprio and Caprice hardware range
- Open-in and Open-out configurations available
- Double rebated frame to seamlessly accommodate Amplimesh security door or flyscreen door
- Bushfire tested to BAL 40

### MAXIMUM PERFORMANCE

| Serviceability Pressure      | 4500Pa  |  |  |
|------------------------------|---------|--|--|
| Ultimate Pressure            | 10000Pa |  |  |
| Water Penetration - open out | 600Pa   |  |  |
| Water Penetration - open in  | 300Pa   |  |  |

# FRAME DIMENSIONS

|                 | Optioni | Option |
|-----------------|---------|--------|
| Frame Depth     | 125mm   | 125mm  |
| Panel Thickness | 36mm    | 46mm   |
|                 |         |        |

# MAXIMUM RECOMMENDED SIZE

|        | Option 1 | Option 2 |
|--------|----------|----------|
| Height | 2700mm   | 3000mm   |
| Width  | 1200mm   | 1200mm   |

## GLAZING CAPACITY

|               | Option I | Option 2 |
|---------------|----------|----------|
| Single Glazed | 4-10mm   | 4-12mm   |
| Thick Glass   | n/a      | 14-18mm  |
| Double Glazed | 16-18mm  | 19-31mm  |

## ACOUSTICS (MAX)

| /(coos //co (w////) |           |
|---------------------|-----------|
| Rw (C;Ctr)          | 33 (0;-1) |

### WINDOW ENERGY RATINGS

|  | Window ID  | Glazing              | Uw   | SHGC | Tvw  | Air Inf |
|--|------------|----------------------|------|------|------|---------|
|  | CAP-508-01 | 6.38Sx Lam           | 5.80 | 0.59 | 0.61 | 0.07    |
|  | CAP-508-03 | 6.38 CP Clr          | 4.40 | 0.49 | 0.57 | 0.07    |
|  | CAP-508-04 | 6Clr                 | 5.90 | 0.59 | 0.61 | 0.07    |
|  | CAP-508-06 | 6Gy                  | 5.90 | 0.42 | 0.61 | 0.07    |
|  | CAP-509-02 | 6.38Sx Lam/12Ar/6Clr | 3.70 | 0.49 | 0.54 | 0.07    |
|  | CAP-509-04 | 6Clr/12Ar/6Clr       | 3.70 | 0.51 | 0.54 | 0.07    |
|  | CAP-509-07 | LB Clr 5/14/5        | 3.00 | 0.41 | 0.54 | 0.07    |
|  | CAP-509-08 | LB Gy 5/14/5         | 3.00 | 0.27 | 0.29 | 0.07    |
|  | CAP-509-26 | AGG PLUS Clr 4/12/4  | 3.00 | 0.43 | 0.55 | 0.07    |
|  | CAP-509-27 | AGG PLUS Clr 5/12/5  | 3.00 | 0.43 | 0.55 | 0.07    |
|  | CAP-509-28 | AGG PLUS Clr 6/12/6  | 3.00 | 0.42 | 0.54 | 0.07    |
|  | CAP-509-30 | AGG PLUS Gy 4/12/4   | 3.00 | 0.31 | 0.35 | 0.07    |
|  | CAP-509-31 | AGG PLUS Gy 6/12/6   | 3.00 | 0.26 | 0.27 | 0.07    |
|  | CAP-509-36 | AGG MAX Clr 6/12/6   | 3.00 | 0.21 | 0.44 | 0.07    |



1800 ALUMINIUM (258 646) capral.com.au Capral Limited ABN 78 004 213 692 June 2021

View full list of Residential WERS ratings at capral.com.au