

**4.5 Inch Adjustable
Fixed Downlight**

Code: D8062S

**Single Light Source
Downlight**



Features

- Latest high performance Chip on Board LED
- Single point light source
- Better performance than a 150w Halogen Par 38 lamp & 2X26w PLC Lamp
- High Power Factor >0.9.

Specification

Light Source	High Bright COB LED
Drive Current	700mA
Power Consumption	20W-25w
Input Voltage/Power Factor	240VAC/>0.95
Color Temperature (CCT)	Warm White 2700±200K
Initial Luminous flux (Total)	2000-2600 lm
Color Rendering index (CRI)	>RA 85 RA90
Luminaire Efficacy	100lm/w
IP Rated	IP20 to IP54
Lens options	30/60 degree Lens

Benefits

- Extra Long Life More than 50,000 hours.
- Save upto 80% of energy Consumption & reduce maintenance costs.
- Virtually no heat or UV output.
- No Mercury & Resistant to Shock and vibration.

Comparison

		
	LED Down Light	Par 38 Halogen Lamp
Power	25w	150 w
Yearly Power Consumption	100 KW	438 KW
Luminous intensity	2400 lms (WW)	2000 lms (WW)
Life span	>50,000 Hrs	<2,000 Hrs
Rohs Compliant	Yes	No

DA Lighting

Unit5, 3 Lancaster Road, Ingleburn NSW 2565

EL: 02 80069016

Email: info@dalighting.net.au

Website: www.dalighting.net.au

4.5 inch Gimble Downlight




Compatibility

Code: D8062S

Dimensions

Dimensions

Hole Cut-Out =
110-120mm



Size:mm

DA Lighting

Unit5, 3 Lancaster Road, Ingleburn NSW 2565

EL: 02 80069016

Email: info@dalighting.net.au

Website: www.dalighting.net.au