



Model:
DHL-9960R
DHL-99100R
DHL-99120R



CE & Energy Star Compliant

IK08 IP40



Features

- Titanium Aluminum Structure
- Extra High performance SMD LEDs with controlled Color consistency and Uniformity
- High-efficiency with accurate light dissipation and modularized design
- UGR 22
- Anti-Corrosion, Anti-UV
- Instant Start
- Warranty: 5 years

Specification

Initial Luminous flux	3300lm / 5300lm
Color Temperature (CCT)	4000K
Dimension (mm)	L: 1200/1500 mm D: \varnothing 60/100/120 mm
Color Rendering index (CRI)	>80/90
Power Consumption	30W / 50W
Power Factor	>0.96
Material	Titanium alloy 6063
Beam Angle	330°
IP Rating Option	IP44

Benefits

- Extra Long Life More than 50,000 hours
- Save up to 80% of energy Consumption & reduce maintenance costs
- Virtually no heat or UV output
- No Mercury & Resistant to Shock and vibration

Optical Performance





Luminaire Categorie:
 Lamp Categorie:
 Lamp Description:
 Number of Lamp:
 Lamp Lumens(lm): 3770.7
 Luminous Length(m): 0.0
 Luminous Width(m): 0.0
 Luminous Height(m): 0.0

Current: 0.171 A
 Power: 36.17 W
 Power Factor: 0.961
 Test Lab:
 Photometric Type: Type C
 Manufacturer:


Photometric Results

CIE Class: Direct
 Luminaire Lumens: 3770.70 lm
 Efficiency: 104.2494 lm/W
 Central Intensity: 798.375cd
 Max. Intensity: 829.347cd
 Field Angle(10%Imax): NA

Max.Intensity Angle: C:0.0 G:8.0
 Beam Angle(50%Imax): 151.34, 131.56
 Luminaire Efficacy Rating(LER) : 100.00%
 Upward Ratio: NA
 Downward Ratio: NA
 Beamwidth(50%Imax): H=151.34V=131.56



Application



Indoors Application



- Showroom
- Product Line, Warehouse
- Shopping Area
- Offices, Education facilities
- Class Room
- Hallway
- Conference Centre

Installation

ROD Suspension

