

A SIKA BRAND

Elite G10 Grout

Premium performance for the perfect finish





BUILDING TRUST

Join the Elite

Introducing Davco Elite G10 Grout, a flexible premium performance grout that offers superior smoothness and maximum colour consistency. Especially formulated with stain, mould and bacteria resistant properties to ensure long lasting performance. Available in a range of contemporary colours to beautifully complement any natural stone, mosaic, ceramic and porcelain tiling project.



*Grout colours are a guide only and may vary to the actual grout colour.

FEATURES AND BENEFITS

- Superior smoothness for easy application
- Maximum colour consistency
- Resistance to efflorescence, cracking and shrinking
- Resistance to stain, mould and bacteria
- Available in a 5kg bag for less waste
- For grout joints 1-8mm wide

WHERE TO USE

Surfaces

Most common tiling substrates.

Tiles

Ideal for all common tiles such as natural stone, marble, porcelain, ceramic and mosaics.

Areas

Suitable for interior and exterior applications. Commercial and domestic walls and floors including high foot traffic locations, bathrooms, kitchens, living rooms, courtyards and swimming pools.

RESOURCES

Technical Data

For application instructions, directions for use and detailed technical specification data visit **sika.com.au**

Technical Support

For product and systems enquiries, please call 1300 22 33 48

Useful Tools

Our Davco Grout Calculator, Grout Colour Selector and System Selector tools make it easy to plan your tiling project. **davcoaustralia.com.au/davco-solutions**

PRODUCT INFORMATION

Coverage Guide

The coverage of the grout will vary depending upon the texture, size and thickness of the tile and the width of the grout joint. Use the table below as a general guide:

Tile Size	Quantity of grout required kg/m ² Joint width			
	1mm	3mm	6mm	8mm
20 x 20 x 8mm	1.8	5.3		
200 x 200 x 8mm	0.2	0.5	1.1	1.4
300 x 300 x 8mm	0.1	0.4	0.7	0.9
300 x 600 x 8mm	0.1	0.3	0.5	0.7
600 x 600 x 8mm	0.1	0.2	0.4	0.5

Technical Data	Elite G10 Grout	
 Final performance after 28 days: Flexural strength Compressive strength Abrasion resistance Shrinkage Water absorption after 30 minutes Water absorption after 4 hours 	Surpasses the requirements of AS ISO 13007.3 CG2 WA	
Appearance	Various coloured powders	
Bulk density	1.4kg/L	
Water resistance	≤5g after 240 min	
Abrasion resistance	≤1000mm³	
Pot life at 20°C	1 hour	
Curing time for dry areas at 20°C	24 hours	
Shelf life when stored unopened in elevated, cool, dry location at 20°C	12 months	

Measurements are taken at 22°C and 50% relative humidity. Specifications vary according to site conditions and should be taken as a guide only.



WE ARE SIKA

Sika is a specialty chemicals company with a leading position in the development and production of systems and products for bonding, sealing, damping, reinforcing and protecting. Our leading technologies service the requirements of Residential and Commercial Building, Mining, Automotive, Industrial Manufacturing and Infrastructure projects around Australia and the world. Sika is a trusted partner to those servicing and specialising in the following markets;





BUILDING TRUST

CONTACT US

With over 100 years experience in supplying products for construction and industry we are confident that we have the perfect solution, no matter what your requirement.



Head Office 55 Elizabeth Street Wetherill Park, NSW 2164 P: (02) 9725 1145

New South Wales

122 Newton Road Wetherill Park, NSW 2164 P: (02) 9725 1700

Queensland

30 Parker Court Pinkenba, QLD 4008 P: (07) 3633 9222 Victoria

33 Fiveways Boulevard Keysborough, VIC 3173 P: (03) 9797 0600

South Australia 28 Kenworth Road Gepps Cross, SA 5094 P: (08) 8162 9055

Western Australia

61 Bushland Ridge Bibra Lake, WA 6163 P: (08) 9395 5300

Sika Australia

1300 22 33 48 sika.com.au



BUILDING TRUST