



Group 1 Fire Rating pre-finished panels for wall & ceiling linings

The FR+ system is a factory-applied, intumescent treatment for Gunnersen's DesignerSolutions interior timber substrates.

Image: Perth Arena

Material: Gunnersen DesignerPly

Note: Typical installation that is suitable for FR+ treatment



GROUP 1
FIRE RATING



NCC-C1:10
INTERIOR STANDARD



CERTIFICATE
OF CONFORMITY



MATERIAL
DESIGN FLEXIBILITY



READY
TO INSTALL





Group 1 Fire Rating

for interior wall and ceiling linings



GROUP 1 FIRE RATING

FR+ treated panels achieve a Group 1 Fire Rating and are ideal for interior wall and ceiling linings.



NCC-C1:10

FR+ treated panels satisfy the requirements of the National Construction Code, Part C1:10.



CERTIFICATE OF CONFORMITY

FR+ treatment has been awarded the Codemark Certificate of Conformity (GM-CM30071-RevA). This has been reviewed and accepted by JAS-ANZ, which is recognised by the ABCB.



MATERIAL DESIGN FLEXIBILITY

Available stocked in Clear and Whitewash finishes on Birch and Hoop substrates. A multitude of substrate and stain options also available for design flexibility.



READY-TO-INSTALL

Product arrives on site pre-finished and ready for installation. No special machinery is required; FR+ is as easy to cut as the non-fire rated substrate.

Current Stock		Available now for delivery and installation	
Substrate	DesignerPly AC Hoop	DesignerPly AB Birch	
Finish	Clear / Whitewash	Clear / Whitewash	
Thickness	12mm	12mm	
Sheet size	2400 x 1200mm	2440 x 1220mm	
Additional		Available by custom order	
DesignerPly	Substrates including: Birch, Hoop & Poplar		
DesignerPanel	Substrates including: MDF, OSB & Particleboard		
DesignerVeneer	Substrates including: MDF, Particleboard & Plywood		
Perforated	Solutions that maintain Group 1 Fire Rating		
How to Specify			
Substrate		Note: 1) Each delivery of material treated with FR+ includes certification complete with supporting documentation. 2) Minimum substrate requirements are 9mm thickness and 380kg/m ³ density	
Treatment	Gunnensen FR+		
Options	[thickness] [sheet size] [finish]		

Speak to your Gunnensen representative for further information and the perfect solution.



AUS web: www.gunnensens.com.au
NZ web: www.gunnensens.co.nz

[instagram.com/gunnensenptyltd](https://www.instagram.com/gunnensenptyltd)
[pinterest.com.au/gunnensen](https://www.pinterest.com.au/gunnensen)

AUS freecall: 1300 088 066
NZ freecall: 0800 448 663

email: enquiries@gunnensen.com.au