

LINEAR (ACTION BAC)



IDENTIFICATION	STANDARD	PRODUCT DATA
Type of manufacture	ISO 2424	woven
Structure	ISO 2424	loop pile
Pile material	ISO 2424	100% PA 6.6 Ascend Ultron®
Dye method		continue dyed
Treatment		
Primary backing	ISO 2424	PP, PES
Secondary backing	ISO 2424	textile
Width	ISO 3018	Ca. 400 cm
Pattern report		-
Effective pile thickness	ISO 1766	Ca. 3,30 mm
Total thickness	ISO 1765	Ca. 4,00 mm
Total pile mass	ISO 2424	Ca. 750 g/m ²
Total mass	ISO 8543	Ca. 2.200 g/m ²
Number of tufts	ISO 1763	Ca. 108.000 /m ²
Stroll test	ISO 6356	≤ 2 kV
Vertical resistance	ISO 10965	
Horizontal resistance	ISO 10965	
Classification for use	EN 1307	33 Commercial - heavy
Luxury rating class	EN 1307	LC1
Impact sound reduction	ISO 10140	ΔL_w ca. 16 dB
Sound absorption	EN ISO 354	0,15 α_w
Thermal conductivity	ISO 8302	Ca. 0,07 m ² K/W
Flammability	EN 13501-1	Cfl - s1
IACG-Nr.		IACG-37-13-01

