



castworks.com.au



ADF have a proud heritage with over 40 years of providing high quality and durable heating systems. Coupled with a sleek European design and manufacture, ADF brings the next level in quality and functionality to the linear wood heater options in the Australian market.

The unique automatic flue damper system significantly reduces smoke ingress to the room on re-fuelling (available on all models). The simplicity in design of the air wash and primary air system belies how well these beautiful fires operate.

## Hayra Freestanding Fire





## Styling options





Hayra 85L Freestanding includes base (optional fan)

Hayra 85B Freestanding (Body) (optional fan)

#### **Dimensions and Specifications**

stal

\* Depth includes a min. 650mm in front of the unit.

## Dade

✓ 5mm steel firebox with matching base High density vermiculite lining system ✓ Removable door tool ✓ Heats up to 200m<sup>2</sup> through natural convection and radiant warmth; boosted by an optional fan



Hayra 85P Freestanding Pedestal



## Linea Freestanding Fires

Linea 85
a second state of the second second second second

## Styling options





Freestanding Pedestal

## Dimensions and Specifications

all dimensions are mm	Linea 85B		Linea 85P Pe	destal	Linea 100B		Linea 100P Pe	edestal
Dimensions (WxHxD - excl. bench)	832 x 465 x 450		832 x 865 x 450		1012 x 465 x 450		1012 x 865 x 450	
Weight	160kg		192kg		175kg		206kg	
Heat Output (Nominal)	13.1kW		13.1kW		17kW		17kW	
Approx. heat area	150 - 200 m <sup>2</sup>		150 - 200 m <sup>2</sup>		200 - 250 m <sup>2</sup>		200 - 250 m <sup>2</sup>	
Efficency	63%		63%		64%		64%	
Emissions	0.8g/Kg		0.8g/Kg		1.2g/Kg		1.2g/Kg	
Flue exit top fits to	200mm		200mm		200mm		200mm	
Optional Fan	Yes		No		Yes		No	
Hearth Dimensions - Thickness (Bellis Board or equivalent)	18mm		18mm		24mm		24mm	
Hearth Dimensions & Clearance Options to combustible wall	Dimensions (WxD)*	Clearance	Dimensions (WxD)*	Clearance	Dimensions (WxD)**	Clearance	Dimensions (WxD)**	Clearance
Parallel no shielding:	1070 x 1500	Sides 475 Rear 400	1070 x 1500	Sides 475 Rear 400	1250 x 1500	Sides 525 Rear 300	1250 x 1500	Sides 525 Rear 300
Parallel with 25mm thick Skamotec wall 1720mm (w) x 1200 (h):	1070 x 1275	Sides 475 Rear 175	1070 x 1275	Sides 475 Rear 175				
Parallel with 25mm thick Skamotec wall 1910mm (w) x 1700 (h):					1250 x 1250	Sides 525 Rear 50	1250 x 1250	Sides 525 Rear 50
Parallel with 180 x 900 s/s rear flue shield and firebox heatshields:	1070 x 1300	Sides 475 Rear 200	1070 x 1300	Sides 475 Rear 200	1250 x 1300	Sides 525 Rear 100	1250 x 1300	Side 525 Rear 100
Steel Bench								
Dimensions (WxDxH)	1010 x 495 x	400	N/A		1200 x 495 x	350	N/A	

\* Depth includes a min. 650mm in front of the unit. \*\* Depth includes a min. 750mm in front of the unit.







Freestanding Bespoke







## Linea Insert Fires



#### Linea 100 Insert Duo



 Double-locking technology, more secure and with concealed design



## Dimensions and Specifications

all dimensions are mm	Linea 85 Insert	Linea 100 Insert	Linea 100 Insert Duo
Dimensions (WxHxD)	832 x 465 x 450	1012 x 465 x 450	1012 x 465 x 550
Weight	158kg	172kg	178kg
Heat Output (Nominal)	13.1kW	17kW	17kW
Approx. heat area	150 - 200 m <sup>2</sup>	200 - 250 m <sup>2</sup>	200 - 250 m <sup>2</sup>
Efficency	63%	64%	-
Emissions	0.8g/Kg	1.2g/Kg	1.2g/Kg
Flue exit top fits to	200mm	200mm	200mm
Fan	Optional Extra	Optional Extra	Optional Extra - Dual Fan
Hearth Dimensions - Thickness (Bellis Board or equivalent)	18mm	24mm	6mm
Hearth Dimensions (WxD)	1070 x 650	1250 x 750	1240 x 300



- Clean glass technology
- 30mm Flat Edge Frame
- 30mm Profil Frame with 20mm Return



• Automatic smoke outlet

adr 🛛

- Pre-regulation draught
- Stainless Steel mechanism

• Tangential fans - efficient and quiet



• Wall mounted touch screen control panel

# <mark>adf</mark>

## About Castworks & ADF

Castworks have been the leading distributor of high quality, European-designed fireplaces for over twenty years and continue to source only the finest products with unique designs and features. Castworks are proud to introduce ADF to their family of products.

Based in Portugal, ADF source only the best components from highly regarded European suppliers allowing for a 5-year warranty on most aspects of the fire.

All units have been tested and comply with AS2918 / AS4012/4013.





#### DISTRIBUTORS FOR



Your ADF dealer

#### Skamol Enclosure for fireplace enclosures



Skamol Enclosure is a light-weight, non-combustible building board that can resist temperatures up to 1000 degrees Celsius. This easy to install product simplifies the construction process by eliminating the need for steel or wood frame constructions. The result is a complete one product solution for your fireplace enclosure that solves a significant challenge facing dealers and installers today – recurring cracks and costly callbacks. When installed correctly, the Skamol Enclosure solution will virtually eliminate cracks.



## One building product multiple design solutions

Due to the strength of Skamol Enclosure, installers are able to apply various finishing materials, e.g. stone and tile. Multiple types of fireplace enclosures can be built using the product.



Most enclosures can be built using only

Skamol Enclosure, replacing the need for light-frame construction and wall covering. This eliminates a complete stage in the construction process, combining multiple building materials into one.

Skamol Enclosure can be used for both traditional and contemporary fireplace installations.

To see more inspiring examples of Skamol Enclosure visit castworks.com.au

The information in this brochure is to assist you in your choice of a suitable fire. It is not intended to be all the information required to install the fire and does not replace the installation manual which provides more detailed information. In the interest of product development ADF reserves the right to change specifications without prior notice.