

PRECISION







PANELS are a prefinished architectural and acoustic system, made to order in Australia.

PANELS are compliant and engineered for performance. They are environmentally certified, Low VOC, fire tested, acoustically rated, and can be modified to achieve various curve radiuses.

Choose from solid timber profiles or fibreboard - prefinished in Olefin decorative film. Group 2 options are available.



gular 5025-6. Navurban™ Albany Oak.

c Design | Eva Shaw





Fire

PANELS are fire tested to AS5637.1 (Group 3). Group 2 fibreboard options are available.



Environment

Solid timber PANELS are PEFC™ certified. Decorative fibreboard PANELS are certified for Global Green Tag™



Emissions

PANELS have been VOC tested and exceed GBCA requirements for commercial fit outs.




Sound Absorption

PANELS have been independently tested and acoustically rated. Please contact us for more information.



Installation

PANELS are supplied as prefinished and assembled modules to enable swift installation. Based upon project requirements, choose from a range of profiles in either solid timber or decorative fibreboard.





DECORATIVE FIBREBOARD EO MR MDF

- Prefinished and assembled
- Custom set outs available
- · Seamless Non-PVC Japanese Olefin Finish
- Group 3 (♦Denotes Group 2 options)

- Acoustically rated
- Green Tag[™] certified
- Low VOC
- Made in Australia

DECORATIVE FIBREBOARD PROFILES

Standard Lengths Derivatives of 2.7m & 3.6m Panel Width 296mm

Square 3232 32x32mm batten

Fluted 2550[♦] 25x50mm batten

3232-4 3232-5

3232-6

2550-3

2550-4

2550-5

17.3mm spacing 42mm spacing 27.2mm spacing

48.7mm spacing 24mm spacing 9.2mm spacing

Half Round 3250 32x50mm batten

Rectangular 2550[♦] 25x50mm batten

3250-3

3250-4

3250-5 2550-3 2550-4

2550-5

48.7mm spacing

24mm spacing

9.2mm spacing

48.7mm spacing

24mm spacing

9.2mm spacing

Rectangular 5025[♦] 50x25mm batten

5025-4

49mm spacing

5025-5

34.2mm spacing

5025-6

24.3mm spacing

Rectangular 9032 90x32mm batten

9032-3 9032-2

116mm spacing

66.7mm spacing



FIBREBOARD FINISHES



Navurban™

Vanilla Bean

Oakwood

Toorak





The Oaks





White



Albany Oak

Ashgrove

Grace





Blackened

American Oak

Earlwood



Tablelands



Clifton Hill

Hollywood

Blackbutt



Black Ravenswood Mountain*

Silken™





Birchgrove



Nutgrove*







Tuscan Grape Jet Black

Elements™





Bronze



*Navurban Diamond™ adds an extra layer of surface protection.

Digital and printed finishes should be used as a guide only. Please request a sample to confirm your selection.

Image: 3040-4. Blackbutt, Clear. High Street | Jackson Clements Burrows Architects | Nicole England











SOLID TIMBER

- Prefinished and assembled
- Custom set outs available
- Group 3
- Acoustically rated

- PEFC[™] certified
- Low VOC
- Made in Australia

SOLID TIMBER PROFILES

Standard Timber Lengths 900mm - 3600mm

Panel Width 296mm

3040 SERIES 28x40mm batten

3060 SERIES 29x60mm batten

3040-4

3040-6

3060-2

3060-3

3060-4

34mm spacing

19.2mm spacing

3040-5

9.3mm spacing

88mm spacing

38.7mm spacing

14mm spacing

4020 SERIES 38x17mm batten

4020-6

32.3mm spacing

4020-7

25.3mm spacing

4020-8

20mm spacing

4030 SERIES 40x28mm batten

4030-4

46mm spacing

31.2mm spacing

4030-5

4030-6

6030 SERIES 60x29mm batten

6030-3

69.7mm spacing

6030-4

45mm spacing

6030-5

30.2mm spacing

9040-2

110mm spacing

9040 SERIES 90x38mm batten

9040-3

60.7mm spacing



SOLID TIMBER FINISHES

Hemlock



Blackbutt

21.3mm spacing

White Wash



Clear



White Wash Warm Grey

Warm Grey

Spotted gum



Walnut



Western red cedar



Walnut



Digital and printed finishes should be used as a guide only. Please request a sample to confirm your selection. Image: 4020-8. Western red cedar, Clear. Juniper Multifunction Centre | H+H Architecture | Lee Griffith







