

SOLIDAL® Smartfix® Captive System

Model	SOLIDAL® Smartfix® T3® CAPTIVE SYSTEM
Material	Solid Aluminium
Thickness	T3® (3mm) & T4® (4mm)
Joint Type	Concealed Weatherseal

Max Length	Up to 1500mm* (Custom)
Max Width	Up to 4500mm* (Custom)
Joint Width	25mm (Joint face cover)

Attachment Methods:

SOLIDAL® Smartfix® System Technology - Mechanically fixed to sub-frame.

Colours and Finishes:

Powder Coat (Akzonobel Interpon / Dulux Duratec, Fluoraset) or PVDF Wet Spray (P.P.G.) in unlimited colours.
Anodised Finish. (Colour matching available)

Compliance:

Non-combustible NCC2019C1.9.
NATA AS1530.1 & AS1530.3 Certified



Supplier: SOLIDAL®

Phone number: 1300 252 325


Email: info@solidal.com

T: 1300 252 325 **E:** info@solidal.com **W:** solidal.com

SPECIFICATION EXAMPLE:

Project X

EXTERNAL FINISHES SCHEDULES

CODE	MATERIAL	AREA	DESCRIPTION	COMMENTS	IMAGE	SUPPLIER	REV
EXTERNAL CLADDING							
EC-100	Aluminium Facade Cladding	Facade	Model: SOLIDAL® Smartfix T3® Captive System Thickness: T3® (3mm) Joint Type: Dry Joint (Rainscreen) Colour: Powdercoat Matt finish / Monument TBC	Compliance: Non-combustible NCC2019C1.9. / NATA AS1530.1 & AS1530.3 Certified		SOLIDAL® info@solidal.com 1300252325	1