

Longevity and
easy maintenance



Flexlight

Perform 702 S2

Applications

- Shade sails
- Shade structures and modular structures
- Restaurant entertaining and dining areas



Longevity and easy maintenance

Provides excellent UV protection and thermal comfort with natural light transmission.

Advantages

- Precontraint® technology offering exceptional dimensional stability and longevity.
- Durable PVDF coating – Easy care maintenance.
- Low Wick treatment ensuring lasting whiteness.
- Resistance to the most demanding environments.
- Excellent natural light transmission.
- Exceptional waterproof, heat reduction and UV protection characteristics.

	■ Technical specifications	Standards
Yarn	1100Dtex PES HT	
Weight	750 g/sqm	EN ISO 2286-2
Width	267 cm	
Standard format length/jumbo rolls	50 lm - 250 lm	
Tensile strength (warp/weft)	280/280 daN/5cm	EN ISO 1421
Tear resistance (warp/weft)	30/28 daN	DIN 53.363
Finish	PVDF	
Visible light transmittance (Tv)	13%	NFP 38511
Flame retardancy AS/NZ 1530.2 AS/NZ 1530.3	Flammability Index 0 Ignitability 17 , Spread of Flame 0 , Heat Evolved 0 , Smoke Developed 5	
Warranty	15 Years Permanent Structures	

The technical data above are average values with +/-5% tolerance.

■ Certifications, labels, guarantees, recycling

ISO 9001
ISO 14001



Precontraint®
technology

15-year
warranty

CSR and LEED reports available on request.

The values above are given as an indication. Our products are subject to changes prompted by technological developments. We reserve the right to modify their characteristics at any time. The buyer of our products is responsible for checking the validity of the above data. Please refer to the text of our warranty. The warranty is valid only after confirmation on case-by-case basis of warranty application. The warranty will not apply to mobile structures.

Serge Ferrari
lightweight + durable

Serge Ferrari SAS
+33 (0)474 974 133
www.sergeferrari.com.au

RAINBOW **SHADE**

0755 805 366
email@rainbowshade.com.au
www.rainbowshade.com.au