



WoodWall

PRODUCT IDENTIFICATION

PRODUCT NAME: WoodWallTM PRODUCT TYPE: Timber Veneer Wallcovering **DISTRIBUTOR**: Elton Group Pty Ltd

COMPOSITION

TYPE OF COMPONENTS	PERCENTAGE OF TOTAL WEIGHT
Poly-urethane Coating	Less than 5%
Veneer	Less than 33%
Ethylene Vinyl Acetate Copolymer	0.09%
Aluminium	0.13%
Craft Paper	0.19%
Ethtylene-Acrylic Acid Polymer	Less than 24%

HAZARDS

FOR HEALTH: None FOR ENVIRONMENT: None PHYSICALLY OR CHEMICALLY: None ANY OTHER OCCASION: None

FIREFIGHTING MEASURES

GROUP NUMBER ASSESSMENT: AS/NZS 3837-1998. Method of test for heat and smoke release rates for materials and products using an oxygen consumption calorimeter. Product Goup Number Classification 2 **EXTINGUISHING MEDIA:** Water, Foam, CO2 **UNUSUAL FIRE AND EXPLOSION HAZARD:** None **SPECIAL FIREFIGHTING PROCEDURES:** Fire fighters should wear self-contained breathing apparatus to avoid inhalation of smoke or vapors

STORAGE AND HANDLING

STORAGE: Store in cool dry location. Keep the product in closed container, such as plastic bag until it is used. **HANDLING:** Avoid direct sunlight, fire, heat, water and high humidity area.

PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Solid, in roll, various colours of face veneer **SPECIFIC GRAVITY:** 0.80 – 0.94 (depending on the species for face veneer) **ODOUR:** a little (non-hazardous) **FLASH POINT:** N/A **EXPLOSION:** None **SOLUBILITY IN WATER:** N/A

STABILITY AND REACTIVITY

STABILITY: Stable HAZARDOUS DECOMPOSITION PRODUCTS: Smoke and fire if ignited HAZARDOUS POLYMERISATION: Will not occur CONDITIONS TO AVOID: Open flame and ignition

This information is furnished without warranty representation, indecent of license if any kind, except that is accurate to the best of Hokusan's knowledge, or obtained from sources believed by Hokusan to be accurate, and Hokusan does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own test.